

OWNER'S MANUAL

FIG0.186 Tc (M) TD -0.0U2 TTD 068Tj0.0L4 Tc (-0.0

! " # \$ % & ' # % () * + , - . / 0 1 # 2 + - . / 3 4 5 6 # 7 8 9 : ;
< = > ? @ A . B C D E F G / H I J K L ! " M N * + >

! " ? @ O P Q R S T 3 4 # U ? V W Q R X Y Z 4 > [\] ' ^ _ ` ! " a b
5 6 c Q R a b 5 6 d \] a b 5 6 > \ a] \$ e f 4 1 5 W # g h \] ? i 6 0 j k l
/ \ m g n > g h \] o p q / r s % t u v ? w x 2 4 0 h >

1.0 / 0 1 2 & ' () 3 4 5 6 7

I

1.18935\$%:

J : ; T5J eqwx 70 OK# h\ a] HKLMNOO#PKQOOpq\
] 7RdQp>

13E! " GWE v ~ k : (LINEE REC)
14E g n s • k : (BAL OUT)
15E F GL MNk I m(MIC IN)
16E HI WOPm(EFX OUT / IN)
17E k I] P G V # DELEGATES &
18E {) P k (DATA)
19E Qp UV(AC220V-240Vy 50Hz-60Hz)

2.0 &' >?

2.1 &. >?

; \mgn/6b78>
I CF\m<F56

2&pW` a56#FIF0&cQ) e4X: /. K5J b{ #J wxX: 34/5J
b{ Y#@YO5J /bZ6. Y^u9[@/i #@c\ :] /5J b{ /Bb>
#?@6[e4

v%- ! &bG# 8' : ; } () ; < * # v%F <b f +LQ&
6. + ~i GZ \ a] ` / HI k : m # EFX OUT & A , i W / ! " E - k I E H
I k I m # EXFIN & A , i W / ! " E - k : OPE (. / LF , i WKO +) >

/O4! " " #/O• " &

a.Z MODE a l x LCD \] ct QR56u

b.Z SAVE a c d >

A